



**KEY FEATURES:**

- 150 PSI NSCWP
- Notched Body Wafer Style
- Short Neck Design

Item	Description	Material
1	Body	Epoxy Coated DI
2	O-Ring	Viton
3	Lower Stem	SS410
4	Disc	WCB+PTFE
5	Seat	PTFE over Silicone
6	Bushing	PTFE
7	Upper Stem	SS410
8	Bolt & Nut	Carbon Steel
9	Locking Plate	Carbon Steel
10	Locking Bolt	Carbon Steel
11	Lever	Malleable Cast Iron
12	Spring Pin	Carbon Steel
13	Greece Fitting	Copper

**SEAT TEMPERATURE RATING (°F)**

PTFE
0° - 350°

Some flow media may further restrict the published temperature limits or significantly reduce seat life.

Size (Inch)	A	B	C	ØD	ØE	N	L	P	W
2	2.99	3.94	1.26	4.75	0.748	4	1.65	10.24	0.354
2-1/2	3.35	4.61	1.26	5.50	0.748	4	1.77	10.24	0.354
3	3.66	4.92	1.26	6.00	0.748	4	1.77	10.24	0.354
4	4.29	6.02	1.26	7.50	0.748	8	2.05	10.24	0.439
5	4.84	6.14	1.26	8.50	0.866	8	2.13	10.24	0.500
6	5.35	6.69	1.26	9.50	0.866	8	2.20	10.24	0.500
8	6.54	9.45	1.50	11.75	0.866	8	2.36	14.17	0.626
10	7.83	11.22	1.50	14.25	0.984	12	2.60	14.17	0.812
12	9.37	11.81	1.50	17.00	0.984	12	3.03	14.17	0.945